



Einhell



EXPERT

Cordless Tile Cutting Machine

TE-TC 18/115 Li-Solo

Item No.: 4301190

Ident No.: 21010

Bar Code: 4006825657500

The Einhell TE-TC 18/115 Li-Solo cordless tile cutting machine, being powered by a rechargeable battery from the high-performance PXC family, is a "lightweight" tool. The tile cutting machine has a parallel stop with a scale and a table which can be tilted and an angle scale from 0° to 45°. The adjustable angle stop has settings from -45° to +45° for miter cuts. An integrated water container provides for cutting disc cooling, and for safety there is a cutting wheel guard. Non-slip, low-vibration feet ensure a secure and steady standing position, and a carrying option for easy transport. The product is supplied complete with a diamond cutting disc and tool. The rechargeable batteries from the PXC series are available separately.

Features & Benefits

- A member of the Power X-Change family
- Flexible use everywhere due to battery motor and low weight
- Tilting table with angle scale (0 - 45°)
- Integrated water tank for cutting disc cooling
- Non-slip and vibration rubber feet for secure hold
- Parallel stop with angle scale for exact straight cuts
- Adjustable (-45° - 45°) angle stop for mitre cuts
- Carrying option for easy transport
- A cutting wheel guard provides the necessary safety
- Complete with diamond cutting disc and a tool for changing
- Supplied without battery and charger (available separately)




Technical Data

- Voltage	18 V
- Speed	3800 min ⁻¹
- Cutting height 45°	16 mm
- Cutting height 90°	24 mm
- Cutting disc	Ø115 x Ø22.2 mm
- Tilting range of included table	45 °
- Working table size	305 x 335 mm
- IP-class	IPX0

Logistic Data

- Product weight (kg)	3.5
- Gross weight (kg)	4.38
- Dimensions single packaging	422 x 410 x 160 mm
- Pieces per export carton	4 Pieces
- Dimensions export carton	440 x 425 x 660 mm
- Container quantities (20"/40"/40"HC)	860 1760 2100



Battery-Running-Times



cutting¹
(pieces)

One Battery for All

1.5 Ah	37
2.0 Ah	50
2.5 Ah	63
3.0 Ah	75
4.0 Ah	100
5.2 Ah	130
6.0 Ah	150
8.0 Ah	200

Test setup:

1) tile - tile 15 mm - Max. electronic speed