



LevelOne 1.25Gbps Single-mode SFP Transceiver, 20km, 1310nm

Brand : LevelOne

Product code: SFP-3211

Product name : 1.25Gbps Single-mode SFP Transceiver, 20km, 1310nm



1.25 Gbps, SFP, LC, 1310nm, 10 km

LevelOne 1.25Gbps Single-mode SFP Transceiver, 20km, 1310nm:

LevelOne SFP-3211 is a high performance and cost-effective single-mode SFP transceiver. Intended for use with Gigabit Ethernet, it provides up to 1.25 Gbps bidirectional data transfer rate on a single duplex fiber core. For use with 9 micron fiber cables, it can reach a distance of up to 10km. The SFP-3211 transceiver operates using a wavelength of 1310nm with a FP Laser Diode light source and has a LC connector.



- 1310nm FPLD
- Data Rate: 1.25Gbps, NRZ
- Single +3.3V Power Supply
- RoHS Compliant and Lead-free
- AC/DC Differential Electrical Interface
- Compliant with Multi-Source Agreement (MSA)
- Duplex LC Connector
- Compliance with specifications for IEEE-802.3z Gigabit Ethernet at 1.25Gbps
- Compliance with ANSI specifications for Fiber Channel applications at 1.06Gbps
- No configuration or installation software required
- Eye Safety Designed to meet LASER Class 1 comply with EN60825-1

Performance		Power	
SFP transceiver type *	Fiber optic	Power over Ethernet (PoE)	✓
Maximum data transfer rate *	1250 Mbit/s	Certificates	
Interface type *	SFP	Compliance certificates	RoHS
Single-mode fiber (SMF) supported	✓	Safety	EN 60825-1
Fiber optic connector	LC	Certification	CE, FCC
Fiber cable diameters supported (core/cladding)	9/125 µm	Operational conditions	
Maximum transfer distance	10000 m	Operating temperature (T-T)	0 - 70 °C
Wavelength	1310 nm	Storage temperature (T-T)	-40 - 85 °C
Tx power (min)	-9.5 dBmW	Operating relative humidity (H-H)	5 - 95%
Tx power (max)	-3 dBmW	Weight & dimensions	
Networking standards	IEEE 802.3z	Width	57 mm
Duplex system	Full	Depth	12 mm
Fiber ports quantity	1	Height	13.7 mm
Features		Weight	20 g
Plug and Play	✓	Packaging data	
Hot-swap	✓	Package width	106 mm
Power		Package depth	20 mm
Input voltage	3.3 V	Package height	65 mm
Maximum voltage	6 V	Package weight	35 g
Maximum current	0.3 A	Logistics data	
		Harmonized System (HS) code	85369010



0878742009144



878742009144



4015867155165

Catalog Object Cloud



Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.